

FISHER

PO BOX 1985
 2060 CAUBLE RD
 SALISBURY, NC 28145
 800-438-6028 PHONE
 800-272-4448 FAX

	WS6 OR WS9 WINDSCREEN	PS6 OR PS9 PRIVACY SCREEN	DMWSBK OR FG DELUXE MESH	MS?? COLORED MESH
FIBER CONTENT	100% PP	100%PP	100% PP	100%PP
CONSTRUCTION	28 X 14	24 X16	9 x 12 1000 D POLYESTER	9 x 9 100 D POLYESTER
WEAVE	NON-LENO	NON-LENO	WEFT INSERTED	WEFT INSERTED
WEIGHT,ADTM D 5261	5.0oz/YD2	5.6oz/YD2	8oz/YD2	6.5oz/YD2
SHADE	75%	92%	75%	35-55% DEPENDING ON COLOR
TENSILE STRENGTH ASTM D 4632 (MD) GRAB METHOD (CD)	300lbs 170lbs	420lbs 225lbs	213 WARP 238 FILL	209 WARP 204 FILL
TEAR STRENGHT ASTM D 4533 (MD) TRAP METHOD (CD)	125lbs 90lbs	125lbs 90lbs	90 +/- 20 90 +/- 20	90 +/- 20 90 +/- 20
AIR FLOW	>300 cfm	>150 cfm	>340 cfm	>460 cfm